

Rockchip Crypto/HWRNG Develop Guide

ID: RK-KF-YF-852

Release Version: V1.2.2

Release Date: 2023-03-15

Security Level: Top-Secret Secret Internal Public

DISCLAIMER

THIS DOCUMENT IS PROVIDED "AS IS". ROCKCHIP ELECTRONICS CO., LTD.("ROCKCHIP")DOES NOT PROVIDE ANY WARRANTY OF ANY KIND, EXPRESSED, IMPLIED OR OTHERWISE, WITH RESPECT TO THE ACCURACY, RELIABILITY, COMPLETENESS, MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR NON-INFRINGEMENT OF ANY REPRESENTATION, INFORMATION AND CONTENT IN THIS DOCUMENT. THIS DOCUMENT IS FOR REFERENCE ONLY. THIS DOCUMENT MAY BE UPDATED OR CHANGED WITHOUT ANY NOTICE AT ANY TIME DUE TO THE UPGRADES OF THE PRODUCT OR ANY OTHER REASONS.

Trademark Statement

"Rockchip", "瑞芯微", "瑞芯" shall be Rockchip's registered trademarks and owned by Rockchip. All the other trademarks or registered trademarks mentioned in this document shall be owned by their respective owners.

All rights reserved. ©2023. Rockchip Electronics Co., Ltd.

Beyond the scope of fair use, neither any entity nor individual shall extract, copy, or distribute this document in any form in whole or in part without the written approval of Rockchip.

Rockchip Electronics Co., Ltd.

No.18 Building, A District, No.89, software Boulevard Fuzhou, Fujian, PRC

Website: www.rock-chips.com

Customer service Tel: +86-4007-700-590

Customer service Fax: +86-591-83951833

Customer service e-Mail: fae@rock-chips.com

Preface

Overview

This document mainly introduces the development of Rockchip Crypto and HWRNG(TRNG), including driver development and upper application development.

Product version

Chipset name	Kernel version
All Rockchip chips with crypto IP	Linux 4.19
All Rockchip chips with crypto IP	Linux 5.10

Intended Audience

This document (this guide) is mainly intended for:

Technical support engineers
Software development engineers

Revision history

Date	Author	Date	Revision description
V1.0.0	Lin Jinhan, Elon Zhang, Wang Xiaobin	2022-01-25	The initial version
V1.1.0	Elon Zhang	2022-02-28	Added a description of user space calling hwrng and other supplementary notes
V1.2.0	Lin Jinhan, Elon Zhang	2022-09-14	1. rk_crypto_mem_alloc added dma-heap allocation support 2. Add support for the cipher aead mode 3. Add support for the rsa algorithm 4. Add support for crypto v3 and trng v1 5. Add log printing level 6. librkcrypto added the kernel version dependency description
V1.2.1	Lin Jinhan	2022-10-09	Fixed description error
V1.2.2	Lin Jinhan	2023-03-15	Add more information to CRYPTO configuration

Contents

[Rockchip Crypto/HWRNG Develop Guide](#)

[Overview](#)

[crypto v1](#)
[crypto v2](#)
[crypto v3](#)

[The crypto IP version of chips](#)

[Driver Development](#)

[Driver Code Description](#)

[hwrng](#)
[crypto](#)

[Enable hwrng](#)

[Menuconfig](#)

[Enable rng node in dts](#)

[Added rng node for new chip](#)

[Verify that HWRNG is enabled](#)

[Enable hardware crypto](#)

[Menuconfig](#)

[Enable crypto node dts](#)

Added crypto node for new chip

Verify that hardware crypto is enabled

User space development

user space invoke hwrng

read kernel driver node

invoke librkcrypto API

user space invoke hardware crypto

Scope of application

Version Dependencies

V1.2.0

Attention

Data Structure

rk_crypto_mem

rk_cipher_config

rk_ae_config

rk_hash_config

rk_rsa_pub_key

rk_rsa_pub_key_pack

rk_rsa_priv_key

rk_rsa_priv_key_pack

Constant

RK_CRYPTO_ALGO

RK_CIPHER_MODE

RK_OEM_HR OTP_KEYID

RK_CRYPTO_OPERATION

RK_RSA_KEY_TYPE

RK_RSA_CRYPT_PADDING

RK_RSA_SIGN_PADDING

Other Constants

API

Data Type

Return Codes

rk_crypto_mem_alloc

rk_crypto_mem_free

rk_crypto_init

rk_crypto_deinit

rk_hash_init

rk_hash_update

rk_hash_update_virt

rk_hash_final

rk_cipher_init

rk_cipher_crypt

rk_cipher_crypt_virt

rk_cipher_final

rk_get_random

rk_write_oem_otp_key

rk_oem_otp_key_is_written

rk_set_oem_hr_otp_read_lock

rk_oem_otp_key_cipher

rk_oem_otp_key_cipher_virt

rk_ae_init

rk_ae_set_aad

rk_ae_set_aad_virt

rk_ae_crypt

rk_ae_crypt_virt

rk_ae_final

rk_rsa_pub_encrypt

rk_rsa_priv_decrypt

[rk_rsa_priv_encrypt](#)
[rk_rsa_pub_decrypt](#)
[rk_rsa_sign](#)
[rk_rsa_verify](#)
[debug log](#)
Hardware Crypto Performance
 [hardware crypto performance under uboot](#)
 [crypto v1 performance](#)
 [crypto v2 performance](#)
[References](#)
[Appendix](#)
 [Professional Term](#)

Overview

There are three versions of crypto IP on the RK platform currently, including crypto V1 / V2 / V3. The V1 and V2 IP versions support different algorithms and use different modes. V3 is based on V2, most of the code can be reuse. Most of the previous hardware random number modules of chip platforms are in the hardware crypto IP. Since RK356x, HWRNG (TRNG) is an independent hardware module.

crypto v1

Algorithm	Description
DES/TDES	Support DES/3DES (ECB and CBC chain mode)
AES	Support AES 128/192/256 bits key mode, ECB/CBC/CTR/XTS chain mode
HASH	Support SHA1/SHA256/MD5 (with hardware padding) HASH function
RSA	Support PKA 512/1024/2048 bit Exp Modulator (RK3126, RK3128, RK3288, and RK3368 are not supported)
TRNG	Support 256 bit True Random Number Generator (TRNG)

crypto v2

Algorithm	Description
DES/TDES	Support ECB/CBC/OFB/CFB mode.
AES	Support ECB/CBC/OFB/CFB/CTR/CTS/XTS/CCM/GCM/CBC-MAC/CMAC mode.
SM4	Support ECB/CBC/OFB/CFB/CTR/CTS/XTS/CCM/GCM/CBC-MAC/CMAC mode. (SM4 is optional)
HASH	Support MD5/SHA1/SHA224/SHA256/SHA384/SHA512/SM3/SHA512-224/SHA512-256 with hardware padding. (SM3 is optional)
HMAC	Support HMAC of SHA-1, SHA-256, SHA-512, MD5, SM3 with hardware padding. (SM3 is optional)
RSA/ECC	Support up to 4096 bits PKA mathematical operations for RSA/ECC/SM2.

Algorithm	Description
TRNG	Support 256 bit True Random Number Generator (TRNG)

crypto v3

On the basis of Crypto V2 algorithm, Crypto V3 add multithreading support. The Cyrpto V3 platform has been able to automatically identify supported algorithms since RV1106, so compatible uses "rockchip,crypto-v3" as the identifier.

The crypto IP version of chips

The crypto IP version of chips show below:

The platforms that use crypto V1 are:

- | RK3399、RK3288、RK3368、RK3328/RK3228H、RK322x、RK3128、RK1108、RK3126

The platforms that use crypto V2 are:

- | RK3326/PX30、RK3308、RK1808、RV1126/RV1109、RK2206、RK356x、RK3588

The platforms that use crypto V3 are:

- | RV1106

Driver Development

Driver Code Description

hwrng

Crypto V1 / V2, TRNGV1, RKRNG four platforms are centralized in the same c file because HWRNG driver is relatively simple.

The driver does not distinguish the specific chip model, only according to `"rockchip,cryptov1-rng"` and `"rockchip,cryptov2-rng"`, `"rockchip,trngv1"`, `"rockchip,rkrng"` four compatible partition. Currently, `'rockchip,trngv1'` and `"rockchip,rkrng"` is a separate HWRNG module, and the other two HWRNG are built into the Crypto module.

Driver Source Code: `drivers/char/hw_random/rockchip-rng.c`

crypto

The current driver implementation algorithm is as follows:

crypto v1:

- **AES:** ECB/CBC
- **DES/TDES:** ECB/CBC
- **HASH:** SHA1/SHA256/MD5

crypto v2: (Some chipset may not support all algorithm)

- **AES:** ECB/CBC/OFB/CFB/CTR/GCM
- **DES/TDES:** ECB/CBC/CFB/OFB
- **SM4:** ECB/CBC/OFB/CFB/OFB/CTR/GCM
- **HASH:** SHA1/SHA256/SHA384/SHA512/MD5/SM3
- **HMAC:** HMAC_SHA1/HMAC_SHA256/HMAC_SHA512/HMAC_MD5/HMAC_SM3
- **RSA:** Support up to 4096 bits key length.

crypto v2/v3 Hardware full version(The mode driver for the following deleted lines has not been implemented yet):

- **AES(128/192/256)**: ECB/CBC/OFB/CFB/CTR/~~XTS/CTS/CCM/GCM/EBC-MAC/CMAC~~
- **SM4**: ECB/CBC/OFB/CFB/CTR/~~XTS/CTS/CCM/GCM/EBC-MAC/CMAC~~
- **DES/TDES**: ECB/CBC/OFB/CFB
- **HASH**: MD5/SHA-1/SHA256/SHA512/SM3/SHA224/SHA384/~~SHA512_224/SHA512_384~~
- **HMAC**: SHA-1/SHA-256/SHA-512/MD5/SM3
- **RSA**: Support up to 4096 bits key length.

crypto v2/v3 Hardware difference table

Chip	AES	DES/TDES	SM3/SM4	HASH	HMAC	RSA	multi-thread
RK3326/PX30/RK3308	√	√	✗	√	√	√	✗
RK1808	AES-128	✗	✗	SHA-1/SHA-224/SHA-256/MD5	✓	✓	✗
RV1126/RV1109	AES-128/AES-256	✓	✓	✓	✓	✓	✗
RK2206	✓	✓	✗	✓	✓	✓	✗
RK3568/RK3588	✓	✓	✓	✓	✓	✓	✗
RV1106	✓	✓	✗	SHA-1/SHA-224/SHA-256/MD5	✓	✓	✓

Note:

1. RK1808 : AES supports only 128bit. For kernel drivers, AES is not supported.
2. RV1126/RV1109: AES-192 is not supported, so the AES-192 part can only be implemented by the soft algorithm, but the soft algorithm cannot support all the modes of the hard algorithm. Therefore, it is recommended not to change the list of configured algorithms in the code.

The driver file are show as below:

```
drivers/crypto/rockchip
|-- procfs.c                                // proc statistics info (clock rate, algo
list, etc.)
|-- procfs.h                                 // proc head file
|-- rk_crypto_bignum.c                         // crypto PKA bignum api
|-- rk_crypto_bignum.h                         // crypto PKA bignum file
|-- rk_crypto_core.c                           // linux crypto Driver framework and public
interface
|-- rk_crypto_core.h                          // linux crypto common head file
|-- rk_crypto_ahash_utils.c                  // ahash common api
|-- rk_crypto_ahash_utils.h                  // ahash common head file
|-- rk_crypto_skcipher_utils.c               // skcipher common api
|-- rk_crypto_skcipher_utils.h               // skcipher common head file
|-- rk_crypto_utils.c                         // crypto common api
|-- rk_crypto_utils.h                         // crypto common head file
|-- rk_crypto_v1.c                            // crypto v1 hardware related interface
implementation
```

```

|-- rk_crypto_v1.h           // crypto v1 structure and interface
declaration
|-- rk_crypto_v1_skcipher.c // crypto v1 block cipher algorithm implement
|-- rk_crypto_v1_ahash.c   // crypto v1 hash algorithm implement
|-- rk_crypto_v1_reg.h     // crypto v1 hardware register definition
|-- rk_crypto_v2.c          // crypto v2 hardware related interface

implementation
|-- rk_crypto_v2.h           // crypto v2 structure and interface
declaration
|-- rk_crypto_v2_skcipher.c // crypto v2 block cipher algorithm implement
|-- rk_crypto_v2_ahash.c   // crypto v2 hash algorithm implement
|-- rk_crypto_v2_akcipher.c // crypto v2 RSA algorithm implement
|-- rk_crypto_v2_pka.c      // crypto v2 pka operation implement
|-- rk_crypto_v2_reg.h     // crypto v2 hardware register definition
|-- rk_crypto_v3.c          // crypto v3 Hardware related interface

implementation
|-- rk_crypto_v3.h           // crypto v3 Structure and interface
declaration
|-- rk_crypto_v3_skcipher.c // crypto v3 block cipher algorithm implement
|-- rk_crypto_v3_ahash.c   // crypto v3 hash algorithm implement
|-- rk_crypto_v3_reg.h     // crypto v3 hardware register definition
`-- cryptodev_linux
space

```

Enable hwrng

Menuconfig

The HWRNG driver is compiled into the kernel by default, and the dts file determines whether to enable it.

The configuration is shown in the following figure (Red marks indicate the configuration path and the options that need to be configured).

The screenshot shows the kernel configuration menu for a Linux arm64 4.4.194 build. The path 'Device Drivers > Character devices > Hardware Random Number Generator Core support' is highlighted with a red box. Below this, a sub-menu titled 'Hardware Random Number Generator Core support' is also highlighted with a red box. It contains two options: 'Timer IOMEM HW Random Number Generator support' and 'Rockchip Random Number Generator support', both of which are marked with a red box.

Or add the following statement to the config file (which is configured by default in rockchip_defconfig):

```

CONFIG_HW_RANDOM=y
CONFIG_HW_RANDOM_ROCKCHIP=y

```

Enable rng node in dts

At present, most chips dtsi file have been configured with HWRNG nodes, and you only need to enable the rng module in the board-level dts, as shown below:

```

&rng {
    status = "okay";
}

```

Added rng node for new chip

Most of the chip platforms have been configured with rng nodes. If the dtsi of chip has not been configured with rng nodes, you can perform the following operations to configure them.

Attention:

1. The RNG base address needs to be modified according to the chip TRM. The RNG base address is the CRYPTO base address.
2. Clocks macros may differ from platform to platform. If there is an error on dts, you can go to the `include/dt-bindings/clock` directory and execute `grep -rn CRYPTO` to find the corresponding clock macros name, as shown below:

```
troy@inno:~/kernel/include/dt-bindings/clock$ grep -rn CRYPTO
rk3328-cru.h:57:#define SCLK_CRYPTO          59
rk3328-cru.h:206:#define HCLK_CRYPTO_MST      336
rk3328-cru.h:207:#define HCLK_CRYPTO_SLV      337
rk3328-cru.h:284:#define SRST_CRYPTO          68
```

crypto v1:

```
rng: rng@ff060000 {
    compatible = "rockchip,cryptov1-rng";
    reg = <0x0 0xff060000 0x0 0x4000>;
    clocks = <&cru SCLK_CRYPTO>, <&cru HCLK_CRYPTO_SLV>;
    clock-names = "clk_crypto", "hclk_crypto";
    assigned-clocks = <&cru SCLK_CRYPTO>, <&cru HCLK_CRYPTO_SLV>;
    assigned-clock-rates = <150000000>, <100000000>;
    status = "disabled";
};
```

crypto v2:

The actual TRNG does not need to rely on all clocks, but only on hclk_crypto

```
rng: rng@ff500400 {
    compatible = "rockchip,cryptov2-rng";
    reg = <0xff500400 0x80>; # Need to add 0x400 if rng is inside crypto
    clocks = <&cru HCLK_CRYPTO>;
    clock-names = "hclk_crypto";
    power-domains = <&power RV1126_PD_CRYPTO>;
    resets = <&cru SRST_CRYPTO_CORE>;
    reset-names = "reset";
    status = "disabled";
};
```

trng v1:

At present, RK3588 and RV1106 use the random number module of TRNG V1, which is completely different from the TRNG module split in Crypto V2 in design and improves the randomness.

```

rng: rng@fe378000 {
    compatible = "rockchip,trngv1";
    reg = <0x0 0xfe378000 0x0 0x200>;
    interrupts = <GIC_SPI 400 IRQ_TYPE_LEVEL_HIGH>;
    clocks = <&scmi_clk SCMI_HCLK_SECURE_NS>;
    clock-names = "hclk_trng";
    resets = <&scmi_reset SRST_H_TRNG_NS>;
    reset-names = "reset";
    status = "disabled";
};

```

Verify that HWRNG is enabled

1. Execute `cat /sys/devices/virtual/misc/hw_random/rng_current` can see the information as the rockchip, determine the current call is hardware driver.
2. linux: execute `cat /dev/hwrng | od -x | head -n 1` will get a row of random numbers, and every time you run it, the content of the random number is different.
3. Android: execute `cat /dev/hw_random | od -x | head -n 1` will get a row of random numbers, and every time you run it, the content of the random number is different.

Enable hardware crypto


Current driver code crypto v1 support rk3328, crypto v2 support px30 / rv1126 / rk3568 / rk3588, crypto v3 support rv1106 . For the above platforms, just enable config and dts node to enable hardware crypto.

The supported features will be reflected in the register information since RV1106, and Crypto V3 can automatically adapt to the new chip.

Menuconfig

After menuconfig configuration, Rockchip crypto driver will be compiled into kernel. It will automatically adapt crypto IP version according to the chip platform compatible ID.

You can see the related configuration items of hardware crypto only after ensuring that `CONFIG_CRYPTO_HW` is enabled.



```

.config - Linux/arm64 5.10.66 Kernel Configuration
> Cryptographic API > Hardware crypto devices
    Hardware crypto devices
    Arrow keys navigate the menu. <Enter> selects submenus --- (or empty submenus ----).
    Highlighted letters are hotkeys. Pressing <Y> includes, <N> excludes, <M> modularizes features.
    Press <Esc><Esc> to exit, <?> for Help, </> for Search. Legend: [*] built-in [ ] excluded
    <M> module < > module capable

    --- Hardware crypto devices
    < > Support for Microchip / Atmel ECC hw accelerator
    < > Support for Microchip / Atmel SHA accelerator and RNG
    [ ] Support for AMD Secure Processor
    < > Support for Cavium CNN55XX driver
    < > Cavium ZIP driver
    <*> Rockchip's Cryptographic Engine driver
    <*> Export rockchip crypto device for user space
    < > Inside Secure's SafeXcel cryptographic engine driver

```

Or add the following statement to the config file. `CONFIG_CRYPTO_DEV_ROCKCHIP_V3` is just an example. You must change it according to the actual chip configuration. It is recommended to use menuconfig, which will automatically select the platform.

```
CONFIG_CRYPTO_HW=y
CONFIG_CRYPTO_DEV_ROCKCHIP=y
CONFIG_CRYPTO_DEV_ROCKCHIP_V3=y
CONFIG_CRYPTO_DEV_ROCKCHIP_DEV=y
```

Enable crypto node dts

After confirming that the crypto dts node is correctly configured, just enable the crypto module in the board-level dts file, as shown in the following:

```
&crypto {
    status = "okay";
};
```

Added crypto node for new chip

If there is no crypto node in chip dtsi file, follow these steps to add support.

1. Determine the version of the chip crypto IP V1 / V2 /V3. V3 version from RV1106, compatible has been determined as `"rockchip,crypto-v3"`, algorithm tailoring and feature are adapted by the software..
2. `drivers/crypto/rockchip/rk_crypto_core.c` add algs_name, soc_data, compatible info.

```
/* Add the algorithm information supported by the chip. Px30 belongs to
crypto V2. For the supported algorithms, see crypto_v2_algs */
/* Attention: Crypto_v2_algs is full algorithms supported by crypto V2. */
/* Some chips are trimmed on Crypto V2. For example, RK1808 does not support
SHA512 algorithm, so it is necessary to compare TRM to confirm the algorithm
supported */
static char *px30_algs_name[] = {
    "ecb(aes)", "cbc(aes)", "xts(aes)",
    "ecb(des)", "cbc(des)",
    "ecb(des3_ede)", "cbc(des3_ede)",
    "sha1", "sha256", "sha512", "md5",
};

/* bind px30_algs_name to px30_soc_data */
static const struct rk_crypto_soc_data px30_soc_data =
    RK_CRYPTO_V2_SOC_DATA_INIT(px30_algs_name, false);

/* bind px30_soc_data to id_table */
static const struct of_device_id crypto_of_id_table[] = {
    /* crypto v2 in belows */
    {
        .compatible = "rockchip,px30-crypto",
        .data = (void *)&px30_soc_data,
    },
    {
        .compatible = "rockchip,rv1126-crypto",
        .data = (void *)&rv1126_soc_data,
    },
    /* crypto v1 in belows */
    {
        .compatible = "rockchip,rk3288-crypto",
        .data = (void *)&rk3288_soc_data,
    },
};
```

```

    .data = (void *)&rk3288_soc_data,
},
{ /* sentinel */
};

```

3. Add crypto node for new chip

Attention:

1. Determine the CRYPTO base address according to the chip TRM
2. Clocks macros may differ from platform to platform. If there is an error on dts, you can go to `include/dt-bindings/clock` and `grep -rn CRYPTO` to find the corresponding clock macros name, as shown below:

```
troy@inno:~/kernel/include/dt-bindings/clock$ grep -rn CRYPTO
rk328-cru.h:57:#define SCLK_CRYPTO          59
rk328-cru.h:206:#define HCLK_CRYPTO_MST      336
rk328-cru.h:207:#define HCLK_CRYPTO_SLV      337
rk328-cru.h:284:#define SRST_CRYPTO          68
```


crypto v1:

```

crypto: crypto-controller@ff8a0000 {                      /* crypto base
address */
    compatible = "rockchip,rk3288-crypto";                  /* platform "rk3399-
crypto" */
    reg = <0x0 0xff8a0000 0x0 0x4000>;                     /* crypto base
address */
    interrupts = <GIC_SPI 48 IRQ_TYPE_LEVEL_HIGH>;           /* crypto interrupts
number */
    clocks = <&cru ACLK_CRYPTO>, <&cru HCLK_CRYPTO>,
              <&cru SCLK_CRYPTO>, <&cru ACLK_DMAC1>;
    clock-names = "aclk", "hclk", "sclk", "apb_pclk";
    resets = <&cru SRST_CRYPTO>;
    reset-names = "crypto-rst";
    status = "disabled";
};
```

crypto v2:

For most crypto V2 chips, the register address of HWRNG is in the middle of crypto. Therefore, you need to split the crypto address space into two parts when configuring reg address. The first part is the register used by the CIPHER and the second part is the register used by RSA.



```

crypto: crypto@ff500000 {
    address /* */                                     /* crypto base
    compatible = "rockchip,rv1126-crypto";           /* modify platform
*/
    reg = <0xff500000 0x400>, <0xff500480 0x3B80>;      /* crypto base
    address /* */
    interrupts = <GIC_SPI 3 IRQ_TYPE_LEVEL_HIGH>;
    clocks = <&cru CLK_CRYPTO_CORE>, <&cru CLK_CRYPTO_PKA>,
              <&cru ACLK_CRYPTO>, <&cru HCLK_CRYPTO>;
    clock-names = "aclk", "hclk", "sclk", "apb_pcclk";
    power-domains = <&power RV1126_PD_CRYPTO>;
    resets = <&cru SRST_CRYPTO_CORE>;
    reset-names = "crypto-rst";
    status = "disabled";
};

```

4. enable crypto node

```

&crypto {
    status = "okay";
};

```

Verify that hardware crypto is enabled

You can view the registered rockchip hardware crypto algorithm by running commands `cat /proc/crypto | grep rk`.(Take RV1126 as an example)

```

driver      : pkcs1pad(rsa-rk,sha256)
driver      : rsa-rk
driver      : hmac-sm3-rk
driver      : hmac-md5-rk
driver      : hmac-sha512-rk
driver      : hmac-sha256-rk
driver      : hmac-sha1-rk
driver      : sm3-rk
driver      : md5-rk
driver      : sha512-rk
driver      : sha256-rk
driver      : sha1-rk
driver      : ofb-des3_edc-rk
driver      : cfb-des3_edc-rk
driver      : cbc-des3_edc-rk
driver      : ecb-des3_edc-rk
driver      : ofb-des-rk
driver      : cfb-des-rk
driver      : cbc-des-rk
driver      : ecb-des-rk
driver      : xts-aes-rk
driver      : ctr-aes-rk
driver      : cfb-aes-rk
driver      : cbc-aes-rk
driver      : ecb-aes-rk
driver      : xts-sm4-rk
driver      : ctr-sm4-rk
driver      : ofb-sm4-rk
driver      : cfb-sm4-rk

```

```
driver      : cbc-sm4-rk
driver      : ecb-sm4-rk
```

You can view the information about the Rockchip crypto driver by running the `cat /proc/rkcrypto` command. (Make sure to update the latest code. The old code does not support this function.) Including crypto version, clock frequency, currently available algorithms, and some statistics of current driver operation, will continue to improve and supplement in the future. ("CRYPTO V3.0.0 multi" indicates that the current platform supports CRYPTO support multithreading).

```
Rockchip Crypto Version: CRYPTO v2.0.0.0
```

```
use_soft_aes192 : false
```

```
clock info:
```

```
    aclk      350000000
    hclk      150000000
    sclk      350000000
    pka       350000000
```

```
valid algorithms:
```

```
    CIPHER:
```

```
        ecb(sm4)
        cbc(sm4)
        cfb(sm4)
        ofb(sm4)
        ctr(sm4)
        ecb(aes)
        cbc(aes)
        cfb(aes)
        ofb(aes)
        ctr(aes)
        ecb(des)
        cbc(des)
        cfb(des)
        ofb(des)
        ecb(des3ede)
        cbc(des3ede)
        cfb(des3ede)
        ofb(des3ede)
```

```
    AEAD:
```

```
        gcm(sm4)
        gcm(aes)
```

```
    HASH:
```

```
        sha1
        sha224
        sha256
        sha384
        sha512
        md5
        sm3
```

```
    HMAC:
```

```
        hmac(sha1)
```

```

        hmac(sha256)
        hmac(sha512)
        hmac(md5)
        hmac(sm3)

    ASYM:
        rsa

Statistic info:
    busy_cnt      : 1
    equeue_cnt    : 28764
    dequeue_cnt   : 28765
    done_cnt      : 310710
    complete_cnt  : 28765
    fake_cnt      : 0
    irq_cnt       : 310710
    timeout_cnt   : 0
    error_cnt     : 0
    last_error    : 0

Crypto queue usage [0/50], ever_max = 1, status: idle

```

User space development

user space invoke hwrng

There are two ways for user space to obtain random numbers output by hwrng:

- read kernel driver node
- invoke librkcrypto API

Attention:

1. After the hwrng hardware driver is successfully registered, entropy can be added to the kernel random driver. The random numbers generated by hwrng are input to the entropy pool of the random driver. The random driver of kernel is CSPRNG (Cryptography Secure Pseudo Random Number Generator), which meets the security standards of cryptography. For high quality random numbers,, you can read `/dev/random` or `/dev/urandom` nodes for random numbers.

read kernel driver node

If the kernel has enabled rng module, random numbers can be obtained by reading nodes in the user space. **Linux reads the node `/dev/hwrng`, Android reads the node `/dev/hw_random`.**
Reference code is as follows:

```

#ifndef ANDROID
#define HWRNG_NODE      "/dev/hw_random"
#else
#define HWRNG_NODE      "/dev/hwrng"
#endif

RK_RES rk_get_random(uint8_t *data, uint32_t len)
{
    RK_RES res = RK_CRYPTO_SUCCESS;
    int hwrng_fd = -1;

```

```

int read_len = 0;

hwrng_fd = open(HWRNG_NODE, O_RDONLY, 0);
if (hwrng_fd < 0) {
    E_TRACE("open %s error!", HWRNG_NODE);
    return RK_CRYPTO_ERR_GENERIC;
}

read_len = read(hwrng_fd, data, len);
if (read_len != len) {
    E_TRACE("read %s error!", HWRNG_NODE);
    res = RK_CRYPTO_ERR_GENERIC;
}

close(hwrng_fd);

return res;
}

```

invoke librkcrypto API

Refer to the API description: [rk_get_random](#).

user space invoke hardware crypto

user space calls the librkcrypto interface to operate the hardware cipher module. This section provides instructions for librkcrypto.

Attention: Check whether hardware crypto has been enabled in the kernel before use, and the enabling method and confirmation method refer to[Enable hardware crypto](#) and [Verify that hardware crypto is enabled](#).

Scope of application

API	RK3588	RK356x	RV1109/1126	others
rk_crypto_mem_alloc/free	√	√	√	
rk_crypto_init/deinit	√	√	√	
rk_get_random	√	√	√	
rk_hash_init/update/update_virt/final	√	√	√	
rk_cipher_init/crypt/crypt_virt/final	√	√	√	
rk_ae_init/set_aad/set_aad_virt/crypt/crypt_virt/final	√	√	√	
rk_rsa_pub_encrypt/priv_decrypt/priv_encrypt/pub_decrypt	√	√	√	
rk_rsa_sign/verify	√	√	√	
rk_write_oem_otp_key	√	√	√	
rk_oem_otp_key_is_written	√	√	√	
rk_set_oem_hr_otp_read_lock	√			
rk_oem_otp_key_cipher	√	√	√	
rk_oem_otp_key_cipher_virt	√	√	√	

Version Dependencies

V1.2.0

Librkcrypto V1.2.0 library functions depend on the following kernel commit points. If the kernel crypto driver is not updated to the following commit points, some functions may be unavailable.

1. kernel 4.19

```
commit c255a0aa097afbf7f28e3c0770c5ab778e5616b2
Author: Lin Jinhan <troy.lin@rock-chips.com>
Date:   Tue Sep 13 17:20:46 2022 +0800

crypto: rockchip: rk3326/px30 add aes gcm support

Signed-off-by: Lin Jinhan <troy.lin@rock-chips.com>
Change-Id: I75949554d4f573c63092841eef76765a69cc6b24
```

2. kernel 5.10

```
commit 47e85085826daf6401265b803ac9ac7116ae6bb4
Author: Lin Jinhan <troy.lin@rock-chips.com>
Date:   Tue Sep 13 17:20:46 2022 +0800

crypto: rockchip: rk3326/px30 add aes gcm support

Signed-off-by: Lin Jinhan <troy.lin@rock-chips.com>
Change-Id: I75949554d4f573c63092841eef76765a69cc6b24
```

Attention

- **The input data length of the symmetric algorithm is required to be consistent with the data length of the selected algorithm and mode.** For example, ECB and CBC require block alignment, while CTS and CTR do not require data length alignment. There's no padding in the API.
- **If the amount of calculated data is pretty large, the algorithm interface that transmits data through dma_fd is recommended to improve the efficiency.** Since crypto only supports contiguous physical addresses up to 4G, the buffer allocated by dma fd must be physically contiguous addresses up to 4G (CMA). It can be allocated using the `rk_crypto_mem` interface provided by librkcrypto, or allocated by yourself using a memory allocation interface such as DRM to get dma fd.
- **CMA config:** Crypto only supports access to CMA addresses up to 4G. If the device uses more than 4G memory, you need to modify the CMA configuration in dts. Otherwise, `rk_crypto_mem` can be allocated successfully, but the allocated memory cannot be used. The following takes rk3588-android.dtsi platform as an example. In the preceding command, 0x10000000 indicates the start address of the CMA (256MB, do not change the value), and 0x00800000 indicates the size of the CMA. You can change the value as required. For details about the CMA, see the documentation <Rockchip_Developer_Guide_Linux_CMA_CN>.

```

--- a/arch/arm64/boot/dts/rockchip/rk3588-android.dtsi
+++ b/arch/arm64/boot/dts/rockchip/rk3588-android.dtsi
@@ -70,7 +70,8 @@
     cma {
         compatible = "shared-dma-pool";
         reusable;

-
+         size = <0x0 (8 * 0x100000)>;
+         //size = <0x0 (8 * 0x100000)>;
+         reg = <0x0 0x10000000 0x0 0x00800000>;
         linux,cma-default;
     };

```

- Before using the following interface, ensure that the TEE function is available. See [<Rockchip_Developer_Guide_TEE_SDK_CN>](#) for details.

```

rk_write_oem_otp_key
rk_oem_otp_key_is_written
rk_set_oem_hr_otp_read_lock
rk_oem_otp_key_cipher
rk_oem_otp_key_cipher_virt

```

- **`rk_set_oem_hr_otp_read_lock`**: If `key_id` is set to `RK_OEM OTP_KEY0/1/2`, the attributes of other OTP areas will be affected after the setting is successful. For example, some OTP regions become unwritable, see the [<Rockchip_Developer_Guide OTP CN>](#) document. Therefore, `RK_OEM OTP_KEY3` is recommended.
- **`rk_oem_otp_key_cipher_virt`**: The maximum `len` value supported is affected by the shared memory of the TEE, which may be smaller than expected if the TEE shared memory is occupied before this interface is used.

Data Structure

`rk_crypto_mem`

```

typedef struct {
    void          *vaddr;
    int           dma_fd;
    size_t        size;
} rk_crypto_mem;

```

- `vaddr` - virtual address of memory
- `dma_fd` - dma_fd of memory
- `size` - size of memory

`rk_cipher_config`

```

typedef struct {
    uint32_t      algo;
    uint32_t      mode;
    uint32_t      operation;
    uint8_t       key[64];
    uint32_t      key_len;
    uint8_t       iv[16];
    void          *reserved;
} rk_cipher_config;

```

- algo - algorithms type, See [RK_CRYPTO_ALGO](#). The actual value range is subject to the API description. The same below.
- mode - algorithms mode, See [RK_CIPHER_MODE](#). Support ECB/CBC/CTR/CFB/OFB/ mode.
- operation - encrypt or decrypt, See [RK_CRYPTO_OPERATION](#).
- key - plaintext key. Invalid when otp key is used.
- key_len - key length (Unit: byte)
- iv - the initial vector is not valid in ECB mode. In other modes, executing `rk_cipher_crypt/crypt_virt` will automatically update iv for multiple segmentation calculations
- reserved - for future use

rk_ae_config

```

typedef struct {
    uint32_t      algo;
    uint32_t      mode;
    uint32_t      operation;
    uint8_t       key[32];
    uint32_t      key_len;
    uint8_t       iv[16];
    uint32_t      iv_len;
    uint32_t      tag_len;
    uint32_t      aad_len;
    uint32_t      payload_len;
    void          *reserved;
} rk_ae_config;

```

- algo - algorithms type, See [RK_CRYPTO_ALGO](#). Support AES/SM4.
- mode - algorithms mode, See [RK_CIPHER_MODE](#). Support GCM/CCM.
- operation - encrypt or decrypt, See [RK_CRYPTO_OPERATION](#).
- key - plaintext key. Invalid when otp key is used.
- key_len - key length (Unit: byte)
- iv - initial vector
- iv_len - initial vector length (Unit: byte)
- tag_len - tag length (Unit: byte)
- aad_len - aad length (Unit: byte)
- payload_len - payload length (Unit: byte)
- reserved - for future use

rk_hash_config

```

typedef struct {
    uint32_t      algo;
    uint8_t       *key;
    uint32_t      key_len;
} rk_hash_config;

```

- algo - algorithms type, See [RK CRYPTO ALGO](#). Support HASH/HMAC.
- key - key for hash-mac, only valid when algo is HMAC
- key_len - key length (Unit: byte)

rk_rsa_pub_key

```

typedef struct {
    const uint8_t   *n;
    const uint8_t   *e;

    uint16_t      n_len;
    uint16_t      e_len;
} rk_rsa_pub_key;

```

- n - module, same as OpenSSL, big-endian mode
- e - exponent, same as OpenSSL, big-endian mode
- n_len - module length
- e_len - exponent length

rk_rsa_pub_key_pack

```

typedef struct {
    enum RK_RSA_KEY_TYPE   key_type;
    rk_rsa_pub_key         key;
} rk_rsa_pub_key_pack;

```

- key_type - key type, See [RK RSA KEY TYPE](#) . Support plaintext key and OTP_KEY encrypted ciphertext key, librkcrypto will pass the key to crypto driver and decrypt it with the corresponding otp key before use.
- key - public key, See [rk_rsa_pub_key](#) .

rk_rsa_priv_key

```

typedef struct {
    const uint8_t   *n;
    const uint8_t   *e;
    const uint8_t   *d;
    const uint8_t   *p;
    const uint8_t   *q;
    const uint8_t   *dp;
    const uint8_t   *dq;
    const uint8_t   *qp;

    uint16_t      n_len;
    uint16_t      e_len;
    uint16_t      d_len;
    uint16_t      p_len;
    uint16_t      q_len;
    uint16_t      dp_len;
}

```

```

    uint16_t      dq_len;
    uint16_t      qp_len;
} rk_rsa_priv_key;

```

- n - module, same as OpenSSL, big-endian mode
- e - exponent, same as OpenSSL, big-endian mode
- d - private key, same as OpenSSL, big-endian mode
- p - optional
- q - optional
- dp - optional
- dq - optional
- qp - optional
- len - the length information of each element will not be described here

rk_rsa_priv_key_pack

```

typedef struct {
    enum RK_RSA_KEY_TYPE      key_type;
    rk_rsa_priv_key          key;
} rk_rsa_priv_key_pack;

```

- key_type - key type, See [RK RSA KEY TYPE](#) . Support plaintext key and OTP_KEY encrypted ciphertext key, librkcrypto will pass the key, with the corresponding otp key decrypted before use.
- key - private key, See [rk rsa_priv key](#) .

Constant

RK_CRYPTO_ALGO

```

/* crypto algorithm */
enum RK_CRYPTO_ALGO {
    RK_ALGO_CIPHER_TOP = 0x00,
    RK_ALGO_AES,
    RK_ALGO_DES,
    RK_ALGO_TDES,
    RK_ALGO_SM4,
    RK_ALGO_CIPHER_BUTT,

    RK_ALGO_HASH_TOP = 0x10,
    RK_ALGO_MD5,
    RK_ALGO_SHA1,
    RK_ALGO_SHA256,
    RK_ALGO_SHA224,
    RK_ALGO_SHA512,
    RK_ALGO_SHA384,
    RK_ALGO_SHA512_224,
    RK_ALGO_SHA512_256,
    RK_ALGO_SM3,
    RK_ALGO_HASH_BUTT,

    RK_ALGO_HMAC_TOP = 0x20,
    RK_ALGO_HMAC_MD5,
    RK_ALGO_HMAC_SHA1,
    RK_ALGO_HMAC_SHA256,
    RK_ALGO_HMAC_SHA512,
}

```

```
RK_ALGO_HMAC_SM3 ,  
RK_ALGO_CMAC_AES ,  
RK_ALGO_CBCMAC_AES ,  
RK_ALGO_CMAC_SM4 ,  
RK_ALGO_CBCMAC_SM4 ,  
RK_ALGO_HMAC_BUTT ,  
};
```

RK_CIPIHER_MODE

```
/* crypto mode */  
enum RK_CIPIHER_MODE {  
    RK_CIPHER_MODE_ECB = 0x00 ,  
    RK_CIPHER_MODE_CBC ,  
    RK_CIPHER_MODE_CTS ,  
    RK_CIPHER_MODE_CTR ,  
    RK_CIPHER_MODE_CFB ,  
    RK_CIPHER_MODE_OFB ,  
    RK_CIPHER_MODE_XTS ,  
    RK_CIPHER_MODE_CCM ,  
    RK_CIPHER_MODE_GCM ,  
    RK_CIPHER_MODE_BUTT  
};
```

RK_OEM_HR OTP_KEYID

```
enum RK_OEM OTP_KEYID {  
    RK_OEM OTP_KEY0 = 0 ,  
    RK_OEM OTP_KEY1 ,  
    RK_OEM OTP_KEY2 ,  
    RK_OEM OTP_KEY3 ,  
  
    RK_OEM OTP_KEY_FW = 10 ,           //key id of fw_encryption_key  
    RK_OEM OTP_KEYMAX  
};
```

RK_CRYPTO_OPERATION

```
/* Algorithm operation */  
#define RK_OP_CIPHER_ENC      1  
#define RK_OP_CIPHER_DEC      0
```

RK_RSA_KEY_TYPE

```
enum RK_RSA_KEY_TYPE {  
    RK_RSA_KEY_TYPE_PLAIN = 0 ,  
    RK_RSA_KEY_TYPE_KEY0_ENC = RK_OEM OTP_KEY0 +1 ,  
    RK_RSA_KEY_TYPE_KEY1_ENC ,  
    RK_RSA_KEY_TYPE_KEY2_ENC ,  
    RK_RSA_KEY_TYPE_KEY3_ENC ,  
    RK_RSA_KEY_TYPE_MAX ,  
};
```

RK_RSA_CRYPT_PADDING

```

enum RK_RSA_CRYPT_PADDING {
    RK_RSA_CRYPT_PADDING_NONE = 0x00, /* without padding */
    RK_RSA_CRYPT_PADDING_BLOCK_TYPE_0, /* PKCS#1 block type 0 padding*/
    RK_RSA_CRYPT_PADDING_BLOCK_TYPE_1, /* PKCS#1 block type 1padding*/
    RK_RSA_CRYPT_PADDING_BLOCK_TYPE_2, /* PKCS#1 block type 2 padding*/
    RK_RSA_CRYPT_PADDING_OAEP_SHA1, /* PKCS#1 RSAES-OAEP-SHA1 padding*/
    RK_RSA_CRYPT_PADDING_OAEP_SHA224, /* PKCS#1 RSAES-OAEP-SHA224 padding*/
    RK_RSA_CRYPT_PADDING_OAEP_SHA256, /* PKCS#1 RSAES-OAEP-SHA256 padding*/
    RK_RSA_CRYPT_PADDING_OAEP_SHA384, /* PKCS#1 RSAES-OAEP-SHA384 padding*/
    RK_RSA_CRYPT_PADDING_OAEP_SHA512, /* PKCS#1 RSAES-OAEP-SHA512 padding*/
    RK_RSA_CRYPT_PADDING_PKCS1_V1_5, /* PKCS#1 RSAES-PKCS1_V1_5 padding*/
};


```

RK_RSA_SIGN_PADDING

```

enum RK_RSA_SIGN_PADDING {
    RK_RSA_SIGN_PADDING_PKCS1_V15_SHA1 = 0x100, /* PKCS#1 RSASSA_PKCS1_V15_SHA1
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_V15_SHA224, /* PKCS#1 RSASSA_PKCS1_V15_SHA224
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_V15_SHA256, /* PKCS#1 RSASSA_PKCS1_V15_SHA256
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_V15_SHA384, /* PKCS#1 RSASSA_PKCS1_V15_SHA384
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_V15_SHA512, /* PKCS#1 RSASSA_PKCS1_V15_SHA512
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_PSS_SHA1, /* PKCS#1 RSASSA_PKCS1_PSS_SHA1
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_PSS_SHA224, /* PKCS#1 RSASSA_PKCS1_PSS_SHA224
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_PSS_SHA256, /* PKCS#1 RSASSA_PKCS1_PSS_SHA256
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_PSS_SHA384, /* PKCS#1 RSASSA_PKCS1_PSS_SHA384
signature*/
    RK_RSA_SIGN_PADDING_PKCS1_PSS_SHA512, /* PKCS#1 RSASSA_PKCS1_PSS_SHA512
signature*/
};


```

Other Constants

```

/* Algorithm block length */
#define DES_BLOCK_SIZE          8
#define AES_BLOCK_SIZE          16
#define SM4_BLOCK_SIZE          16
#define SHA1_HASH_SIZE          20
#define SHA224_HASH_SIZE        28
#define SHA256_HASH_SIZE        32
#define SHA384_HASH_SIZE        48
#define SHA512_HASH_SIZE        64
#define MD5_HASH_SIZE           16
#define SM3_HASH_SIZE           32
#define AES_AE_DATA_BLOCK       128
#define MAX_HASH_BLOCK_SIZE     128
#define MAX_TDES_KEY_SIZE       24
#define MAX_AES_KEY_SIZE        32
#define MAX_AE_TAG_SIZE         16

```

```
#define RSA_BITS_1024          1024
#define RSA_BITS_2048          2048
#define RSA_BITS_3072          3072
#define RSA_BITS_4096          4096
#define MAX_RSA_KEY_BITS      RSA_BITS_4096

#define RK_CRYPTO_MAX_DATA_LEN (1 * 1024 * 1024)
```

API

Data Type

```
typedef uint32_t RK_RES;
typedef uint32_t rk_handle;
```

Return Codes

```
/* API return codes */
#define RK_CRYPTO_SUCCESS          0x00000000
#define RK_CRYPTO_ERR_GENERIC       0xF0000000
#define RK_CRYPTO_ERR_PARAMETER     0xF0000001
#define RK_CRYPTO_ERR_STATE         0xF0000002
#define RK_CRYPTO_ERR_NOT_SUPPORTED 0xF0000003
#define RK_CRYPTO_ERR_OUT_OF_MEMORY 0xF0000004
#define RK_CRYPTO_ERR_ACCESS_DENIED 0xF0000005
#define RK_CRYPTO_ERR_BUSY           0xF0000006
#define RK_CRYPTO_ERR_TIMEOUT        0xF0000007
#define RK_CRYPTO_ERR_UNINITED       0xF0000008
#define RK_CRYPTO_ERR_KEY            0xF0000009
#define RK_CRYPTO_ERR_VERIFY          0xF000000A
#define RK_CRYPTO_ERR_PADDING          0xF000000B
#define RK_CRYPTO_ERR_PADDING_OVERFLOW 0xF000000C
#define RK_CRYPTO_ERR_MAC_INVALID    0xF000000D
```

rk_crypto_mem_alloc

```
rk_crypto_mem *rk_crypto_mem_alloc(size_t size);
```

function

To request a block of memory, `rk_crypto_mem` is returned, which contains the virtual address of the memory and `dma_fd`.

parameters

- [in] `size` - size of the memory to be alloced
- [out] `memory` - memory address info, See [rk_crypto_mem](#) .

Attention

1. The maximum memory size depends on the kernel CMA buffer size and usage.

rk_crypto_mem_free

```
void rk_crypto_mem_free(rk_crypto_mem *memory);
```

function

Free the memory allocated by `rk_crypto_mem_alloc`.

parameters

- [in] memory - memory address info, See [rk_crypto_mem](#) .

`rk_crypto_init`

```
RK_RES rk_crypto_init(void);
```

function

crypto initialization, such as open device nodes, etc.

parameters

- None

`rk_crypto_deinit`

```
void rk_crypto_deinit(void);
```

function

Release crypto resources, such as close device nodes.

parameters

- None

`rk_hash_init`

```
RK_RES rk_hash_init(rk_hash_config *config, rk_handle *handle);
```

function

Initializes the hash algorithm, support MD5/SHA1/SHA224/SHA256/SHA384/SHA512/SM3.

parameters

- [in] config - hash/hmac configure
- [out] handle - hash/hmac handle

Attention

1. After `rk_hash_init` succeeds, `rk_hash_final` must be called to destroy resources regardless of whether `rk_hash_update()` or `rk_hash_update_virt` was executed successfully or not.
2. If `rk_hash_init` returns RK_CRYPTO_ERR_BUSY, the platform does not support multithreading and only one handle can work at a time. You need to wait for the previous handle to be released before applying for a new handle.

`rk_hash_update`

```
RK_RES rk_hash_update(rk_handle handle, int data_fd, uint32_t data_len);
```

function

Receive dma_fd of data as input, calculates the hash/hmac value, and supports multiple packet calculations.

parameters

- [in] handle - hash/hmac handle
- [in] data_fd - handle of data to be calculated
- [in] data_len - data length (Unit: byte)

Attention

1. handle must be initialized with `rk_hash_init()`.
2. It can be called multiple times to feed the data that needs to be computed.
3. The data length data_len must be 64 bytes aligned if data is not the last group of data.

`rk_hash_update_virt`

```
RK_RES rk_hash_update_virt(rk_handle handle, uint8_t *data, uint32_t data_len);
```

function

Receive virtual address data as input and computes the hash value. Supports multiple packet computations.

parameters

- [in] handle - hash/hmac handle
- [in] data - data to be calculated
- [in] data_len - data length (Unit: byte)

Attention

1. handle must be initialized with `rk_hash_init()`.
2. It can be called multiple times to feed the data that needs to be computed.
3. The data length data_len must be 64 bytes aligned if data is not the last group of data.

`rk_hash_final`

```
RK_RES rk_hash_final(rk_handle handle, uint8_t *hash);
```

function

After all the data is computed, the interface is called to get the final hash/hmac value and release the handle. If you need to interrupt the computation, you must also call this interface to end the hash computation.

parameters

- [in] handle- hash/hmac handle
- [out] hash - output of hash/hmac

Attention

1. handle must be initialized with `rk_hash_init()`.
2. The hash/hmac output buffer size must be greater than or equal to the hash length.

`rk_cipher_init`

```
RK_RES rk_cipher_init(rk_cipher_config *config, rk_handle *handle);
```

function

Initialize symmetric cipher algorithms. Support TDES/AES/SM4 algorithms type. Support ECB/CBC/CTR/CFB/OFB mode.

parameters

- [in] config - algorithm, pattern, key, iv, etc. See [rk_cipher_config](#)
- [out] handle - handle of cipher

Attention

1. After init succeeds, `rk_cipher_final()` must be called to destroy the related resources, regardless of whether `rk_cipher_crypt/crypt_virt()` was successfully executed.

rk_cipher_crypt

```
RK_RES rk_cipher_crypt(rk_handle handle, int in_fd, int out_fd, uint32_t len);
```

function

Receive dma_fd of data to perform encryption and decryption by using symmetric cipher algorithm.

parameters

- [in] handle - handle of cipher
- [in] in_fd - dma_fd of input data
- [out] out_fd - dma_fd of output data
- [in] len - input data length(Unit: byte)

Attention

1. handle must be initialized with `rk_cipher_init()`.
2. in_fd and out_fd can be the same dma_fd.
3. After the calculation, iv in `rk_cipher_config` will be updated. Repeat many times, can realize the segmented call.

rk_cipher_crypt_virt

```
RK_RES rk_cipher_crypt_virt(rk_handle handle, const uint8_t *in, uint8_t *out, uint32_t len);
```

function

Receive virtual address of data to perform encryption and decryption by using symmetric cipher algorithm.

parameters

- [in] handle - handle of cipher
- [in] in - input data buffer
- [out] out - output data buffer
- [in] len - input data length (Unit: byte)

Attention

1. handle must be initialized with `rk_cipher_init()`.
2. input and output can be the same buffer.

3. After the calculation, iv in `rk_cipher_config` will be updated. Repeat many times, can realize the segmented call.

rk_cipher_final

```
RK_RES rk_cipher_final(rk_handle handle);
```

function

End the calculation process and release the handle.

parameters

- [in] handle - handle of cipher that must be initialized with `rk_cipher_init()`.

rk_get_random

```
RK_RES rk_get_random(uint8_t *data, uint32_t len)
```

function

Gets a random number of the specified length from HWRNG.

parameters

- [out] data - random data
- [in] len - the length of the random number to get (Unit: byte)

rk_write_oem_otp_key

```
RK_RES rk_write_oem_otp_key(enum RK_OEM OTP_KEYID key_id, uint8_t *key,
                           uint32_t key_len);
```

function

Writes the key in plaintext to the specified OEM OTP region.

For details of OEM OTP features, see <Rockchip_Developer_Guide OTP_CN>.

parameters

- [in] key_id - the key region index to be written
- [in] key - plaintext of key
- [in] key_len - plaintext key length (Unit: byte)

Attention

1. Key_id supports four keys `RK_OEM OTP_KEY0 - 3` by default. For RV1126 / RV1109, key_id `RK_OEM OTP_KEY_FW` is supported. `RK_OEM OTP_KEY_FW` is the key used by BootROM to decrypt loader. `rk_oem_otp_key_cipher_virt` supports the encryption and decryption of service data using this key.
2. For `RK_OEM OTP_KEY_FW`, key_len supports 16 byte. For other keys, key_len supports 16, 24, and 32 byte.

rk_oem_otp_key_is_written

```
RK_RES rk_oem_otp_key_is_written(enum RK_OEM OTP_KEYID key_id, uint8_t
                                  *is_written);
```

function

Check whether the key has been written to the specified OEM OTP area.

For details of OEM OTP features, see <Rockchip_Developer_Guide OTP_CN>.

parameters

- [in] key_id - the key region index to be written
- [out] is_written - check whether the secret key has been written. 1 indicates that the secret key has been written. 0 indicates that the secret key has not been written.

return value

is_written values are meaningful only when the return value is `#define RK_CRYPTO_SUCCESS 0x00000000`.

The RK3588 platform also checks whether the key_id is locked. If the key_id is locked, error `#define RK_CRYPTO_ERR_ACCESS_DENIED 0xF0000005` is displayed.

Attention

1. key_id supports four keys `RK_OEM OTP_KEY0 - 3` by default. For RV1126/RV1109, the key whose key_id is `RK_OEM OTP_KEY_FW` is supported.

`rk_set_oem_hr_otp_read_lock`

```
RK_RES rk_set_oem_hr_otp_read_lock(enum RK_OEM OTP_KEYID key_id);
```

function

Set the read lock flag for the specified OEM OTP area. After the read lock flag is set successfully, the OTP area is forbidden to write data, and the existing data in the OTP area is unreadable by CPU software. You can use the key through the `rk_oem_otp_key_cipher_virt` interface.

For details of OEM OTP features, see <Rockchip_Developer_Guide OTP_CN>.

parameters

- [in] key_id - The key_id to be set supports `RK_OEM OTP_KEY0 - 3`

`rk_oem_otp_key_cipher`

```
RK_RES rk_oem_otp_key_cipher(enum RK_OEM OTP_KEYID key_id, rk_cipher_config *config,
                           int32_t in_fd, int32_t out_fd, uint32_t len);
```

function

Select the key in the OEM OTP area and perform single cipher calculation in dma_fd mode.

parameters

- [in] key_id - the otp key index to use
- [in] config - algorithm, pattern, key, iv, etc
- [in] in_fd - dma_fd of input which can be the same as output
- [out] out_fd - dma_fd of output
- [in] len - input data length (Unit: byte)

Attention

1. Key_id supports `RK_OEM OTP KEY0 - 3` by default. For RV1126 / RV1109, `RK_OEM OTP KEY_FW` is supported.
2. Support AES/SM4 algorithms type and ECB/CBC/CTS/CTR/CFB/OFB mode.
3. The key length can be 16, 24, or 32 bytes. On the RV1109/RV1126 platform, the key length can be 16 or 32 bytes. When the key_id is `RK_OEM OTP KEY_FW`, the key length can be 16 bytes.
4. in_fd and out_fd can be the same.

rk_oem_otp_key_cipher_virt

```
RK_RES rk_oem_otp_key_cipher_virt(enum RK_OEM OTP_KEYID key_id, rk_cipher_config
*config,
                                uint8_t *src, uint8_t *dst, uint32_t len);
```

function

Select the key in the OEM OTP area, and perform single cipher calculation in virtual addr mode.

parameters

- [in] key_id -the otp key index to use
- [in] config - algorithm, pattern, key, iv, etc
- [in] src - input data buffer
- [out] dst - output data buffer
- [in] len - input data length (Unit: byte)

Attention

1. Key_id supports `RK_OEM OTP KEY0 - 3` by default. For RV1126 / RV1109, `RK_OEM OTP KEY_FW` is supported.
2. Support AES/SM4 algorithms type and ECB/CBC/CTS/CTR/CFB/OFB mode.
3. The key length can be 16, 24, or 32 bytes. On the RV1109/RV1126 platform, the key length can be 16 or 32 bytes. When the key_id is `RK_OEM OTP KEY_FW`, the key length can be 16 bytes.
4. in_fd and out_fd can be the same.
5. The default maximum length of the input and output buffers len is 1MB. For RV1126/RV1109, len is 500KB.

rk_ae_init

function

AEAD algorithms initialization. AES/SM4 is supported. Currently, only GCM is supported.

parameters

- [in] config - algorithm, mode, key, iv, aad length, tag length, etc. See [rk_ae_config](#) .
- [out] handle - handle of AEAD

Attention

After init succeeds, you must call `rk_ae_final()` to destroy resources regardless of whether subsequent execution succeeds.

rk_ae_set_aad

```
RK_RES rk_ae_set_aad(rk_handle handle, int aad_fd);
```

function

Receiving dma_fd of data and sets aad parameters.

parameters

- [in] handle - handle of cipher
- [in] aad_fd - dma_fd of aad data

Attention

1. handle must be initialized with `rk_ae_init()`.
2. Currently, `rk_ae_set_aad` can only be called once after `rk_ae_init`. Multiple AAD data updates are not supported. Multiple updates cause the contents of AAD to be overwritten.

`rk_ae_set_aad_virt`

```
RK_RES rk_ae_set_aad_virt(rk_handle handle, uint8_t *aad_virt);
```

function

Receiving virtual address to sets AAD data.

parameters

- [in] handle - handle of cipher
- [in] in - buffer of aad data

Attention

1. handle must be initialized with `rk_ae_init()`.
2. Currently, `rk_ae_set_aad_virt` can only be called once after `rk_ae_init`. Multiple AAD data updates are not supported. Multiple updates cause the contents of AAD to be overwritten.

`rk_ae_crypt`

```
RK_RES rk_ae_crypt(rk_handle handle, int in_fd, int out_fd, uint32_t len,
                    uint8_t *tag);
```

function

AEAD algorithm is used to perform encryption and decryption and tag calculation/verification for receiving dma_fd of data.

parameters

- [in] handle - handle of ae
- [in] in_fd - dma_fd of input data
- [out] out_fd - dma_fd of output data
- [in] len - input data length(Unit: byte)
- [in/out] tag - input for encryption, output for decryption

Attention

1. handle must be initialized with `rk_ae_init()`.
2. in_fd and out_fd can be the same dma_fd.
3. Multiple call segments are not supported.

`rk_ae_crypt_virt`

```
RK_RES rk_ae_crypt_virt(rk_handle handle, const uint8_t *in, uint8_t *out,  
uint32_t len, uint8_t *tag);
```

function

AEAD algorithm is used to encrypt and decrypt virtual address data.

parameters

- [in] handle - handle of ae
- [in] in - input buffer
- [out] out - output buffer
- [in] len - input data length(Unit: byte)
- [in/out] tag - input for encryption, output for decryption

Attention

1. handle must be initialized with `rk_ae_init()`.
2. input and output can be the same buffer..
3. Multiple call segments are not supported.

`rk_ae_final`

```
RK_RES rk_ae_final(rk_handle handle);
```

function

End the calculation process and release the handle.

parameters

- [in] handle - handle of AE that must be initialized with `rk_ae_init()`.

`rk_rsa_pub_encrypt`

```
RK_RES rk_rsa_pub_encrypt(const rk_rsa_pub_key_pack *pub, enum  
RK_RSA_CRYPT_PADDING padding, const uint8_t *in, uint32_t in_len, uint8_t *out,  
uint32_t *out_len);
```

function

The public key is used to encrypt data, and encryption padding is supported.

parameters

- [in] pub - rsa public key information. See [rk_rsa_pub_key_pack](#).
- [in] padding - encrypt padding type. See [RK RSA CRYPT PADDING](#).
- [in] in - input data
- [in] in_len - input data length(Unit: byte). If the input data is too long, the error code `RK_CRYPTO_ERR_PADDING_OVERFLOW` is returned.
- [out] out - ciphertext encrypted by the public key
- [out] out_len - ciphertext length

Attention

1. The public key must be set correctly to specify whether the key is in plaintext or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. In-situ encryption and decryption are not recommended.

rk_rsa_priv_decrypt

```
RK_RES rk_rsa_priv_decrypt(const rk_rsa_priv_key_pack *priv, enum  
RK_RSA_CRYPT_PADDING padding, const uint8_t *in, uint32_t in_len, uint8_t *out,  
uint32_t *out_len);
```

function

The private key is used to decrypt the data, and padding parsing is supported.

parameters

- [in] priv - rsa private key information. See [rk_rsa_priv_key_pack](#)
- [in] padding - the padding type must be the same as the encryption padding. See [RK RSA CRYPT_PADDING](#)
- [in] in - input data
- [in] in_len - input data length(Unit: byte)
- [out] out - plaintext decrypted by private key
- [out] out_len - plaintext length

Attention

1. The private key must be set correctly to specify whether the key is in plain text or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. In-situ encryption and decryption are not recommended.

rk_rsa_priv_encrypt

```
RK_RES rk_rsa_priv_encrypt(const rk_rsa_priv_key_pack *priv, enum  
RK_RSA_CRYPT_PADDING padding, const uint8_t *in, uint32_t in_len, uint8_t *out,  
uint32_t *out_len);
```

function

The private key is used to encrypt data, and encryption padding is supported.

parameters

- [in] priv - rsa private key information. See [rk_rsa_priv_key_pack](#)
- [in] padding - encrypt padding type. See [RK RSA CRYPT_PADDING](#)
- [in] in - input data
- [in] in_len - input data length(Unit: byte). If the input data is too long, the error code [RK_CRYPTO_ERR_PADDING_OVERFLOW](#) is returned.
- [out] out - ciphertext encrypted by the private key
- [out] out_len - ciphertext length

Attention

1. The private key must be set correctly to specify whether the key is in plain text or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. In-situ encryption and decryption are not recommended.

rk_rsa_pub_decrypt

```
RK_RES rk_rsa_pub_decrypt(const rk_rsa_pub_key_pack *pub, enum  
RK_RSA_CRYPT_PADDING padding, const uint8_t *in, uint32_t in_len, uint8_t *out,  
uint32_t *out_len);
```

function

The public key is used to decrypt the data, and padding parsing is supported.

parameters

- [in] pub - rsa public key information. See [rk_rsa_pub_key_pack](#).
- [in] padding - the padding type must be the same as the encryption padding. see [RK RSA CRYPT_PADDING](#)
- [in] in - input data
- [in] in_len - input data length(Unit: byte)
- [out] out - plaintext decrypted by public key
- [out] out_len - plaintext length

Attention

1. The public key must be set correctly to specify whether the key is in plain text or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. In-situ encryption and decryption are not recommended.

[rk_rsa_sign](#)

```
RK_RES rk_rsa_sign(const rk_rsa_priv_key_pack *priv, enum RK_RSA_SIGN_PADDING padding, const uint8_t *in, uint32_t in_len, const uint8_t *hash, uint8_t *out, uint32_t *out_len);
```

function

Use the private key pair to calculate the hash of input data or use the external hash value for signature.

parameters

- [in] priv - rsa private key information. See [rk_rsa_priv_key_pack](#)
- [in] padding - signature padding type. See [RK RSA SIGN_PADDING](#)
- [in] in - input data will calculating hash first and signed by private key (optional)
- [in] in_len - input data length (Unit: byte)
- [in] hash - hash value(optional), the hash length is determined according to the padding algorithm, and the hash value can be signed directly by using the private key
- [out] out - signature data signed using the private key
- [out] out_len - signature data length

Attention

1. The private key must be set correctly to specify whether the key is in plain text or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. When `in != NULL && hash == NULL`, the interface calculates the hash value of input data (the hash algorithm is determined by the padding format) and then executes the padding signature on the hash value.
3. The interface padding the incoming hash value directly if `hash != NULL`.

[rk_rsa_verify](#)

```
RK_RES rk_rsa_verify(const rk_rsa_pub_key_pack *pub, enum RK_RSA_SIGN_PADDING padding, const uint8_t *in, uint32_t in_len, const uint8_t *hash, uint8_t *sign, uint32_t sign_len);
```

function

Verify the signature using the public key.

parameters

- [in] pub - rsa public key information. See [rk_rsa_pub_key_pack](#).
- [in] padding - the padding type must be the same as the signing padding. See [RK RSA SIGN PADDING](#)
- [in] in - input data will calculating hash first and signed by private key (optional)
- [in] in_len - input data length (Unit: byte)
- [in] hash - hash value(optional)
- [in] sign - signature data
- [in] sign_len - signature data length (Unit: byte)

Attention

1. The public key must be set correctly to specify whether the key is in plain text or the ciphertext encrypted by OTP KEY. This step will affect key parsing.
2. When `in != NULL && hash == NULL`, the interface calculates the hash value of in (the hash algorithm is determined by the padding format) and then executes the padding verify the hash value.
3. The interface padding the incoming hash value directly if `hash != NULL`.

debug log

librkcrypto logs are currently divided into the following levels.

```
enum RKCRYPTO_TRACE_LEVEL {
    TRACE_TOP      = 0,
    TRACE_ERROR    = 1,
    TRACE_INFO     = 2,
    TRACE_DEBUG    = 3,
    TRACE_VERBOSE  = 4,
    TRACE_BUTT,
};
```

The default log level is `TRACE_INFO`. You can change the log level by setting the environment variable (which must be set before the librkcrypto library is loaded). It can also be set through the `rkcrypto_set_trace_level` interface before `rk_crypto_init`.

Android:

```
setprop vendor.rkcrypto.trace.level 1/2/3/4
```

Linux:

```
export rkcrypto_trace_level=1/2/3/4
```

Hardware Crypto Performance

hardware crypto performance under uboot

crypto v1 performance

Test environment (uboot RK3399):

Clock Rate: CRYPTO_CORE = 200M, The highest frequency varies slightly from chip to chip.

CIPHER/HASH Performance:

ALGO	Actual (MBps)	Theoretical (MBps)
DES	-	<=94
TDES	-	<=31
AES-128	-	<=290
AES-192	-	<=246
AES-256	-	<213
MD5	125	<196
SHA1	125	<158
SHA256	125	-

RSA Performance:

RSA key length (nbits)	pub enc/priv dec (ms)
2048	8 / 632

crypto v2 performance

Test environment (uboot RV1126) :

Clock Rate: CRYPTO_CORE = 200M, CRYPTO_PKA=300M, DDR=786M

Hash/HMAC: A total of 128M data is tested, and 4M data is calculated each time.

DES/3DES/AES/SM4: A total of 128M data is tested, 4M plaintext and 4M aad data are calculated each time.

ALGO	MODE	Actual (MBps)			Theoretical (MBps)		
HASH/HMAC	MD5	183			196		
	SHA1	148			158		
	SHA256/224	183			196		
	SHA512/384/512_224/512_256	288			316		
	SM3	183			-		
DES	ECB	289			352		
	CBC/CFB/OFB	79			88		
3DES	ECB	107			116		
	CBC/CFB/OFB	27			29		
AES (128 192 256)	ECB/CTR/XTS	447	442	436	1066	914	800
	CBC/CFB/OFB/CTS	234	204	180	266	228	200
	CMAC/CBC_MAC	245	212	186	266	228	200
	CCM(data+aad)	180	162	146	-	-	-
	GCM(data+aad)	196	184	174	-	-	-
SM4	ECB/CTR/XTS	320			-	-	-
	CBC/CFB/OFB/CTS	87			-	-	-
	CMAC/CBC_MAC	89			-	-	-
	CCM(data+aad)	156			-	-	-
	GCM(data+aad)	114			-	-	-

RSA test: Generate rsa keys, including n, e, and d, and perform public key encryption and private key decryption tests

Public key encrypt: ciphertext = $d^e \% n$

Private key decrypt: plaintext = $d^d \% n$

References

Appendix

Professional Term